

NOTES:

1. ALL WWI TREE MARKERS TO BE TAKEN UP DURING DEMOLITION, PRESERVED, AND REINSTALLED AT CURRENT LOCATION.
2. ROOF DRAINS TO BE ROUTED UNDER SIDEWALK AND DRAINED TO FACE OF CURB AS NEEDED.
3. NO ERROR OR OMISSION IN EITHER THE PLANS, CALCULATIONS OR APPLICATIONS (WHETHER THESE PLANS, CALCULATIONS OR APPLICATIONS HAVE BEEN REVIEWED BY THE CITY OR NOT) SHALL PERMIT OR RELEASE THE CONTRACTOR FROM CONSTRUCTING THIS WORK IN ANY OTHER MANNER THAN THAT PROVIDED FOR IN THE CITY ORDINANCES.



Perry Eisenach, PE
Public Services Director
City of Winchester

[illegible]

**CITY OF
WINCHESTER
VIRGINIA**



SHEET: 1 / 5



REVISIONS			
NO.	DATE	DESCRIPTION	BY


HANDLEY BOULEVARD
IMPROVEMENTS

WINCHESTER, VIRGINIA

PROJECT LAYOUT

CITY OF
WINCHESTER
VIRGINIA

ENGINEERING DIVISION
15 N. CAMERON STREET
WINCHESTER, VA 22601
PH: (540) 667-1815
FAX: (540) 662-3351



DRAWN BY: PROJECT NO:
rab

SCALE: DATE:
1" = 20' 3/17/16

SHEET:
2/ 5



REVISIONS			
NO.	DATE	DESCRIPTION	BY

HANDLEY BOULEVARD IMPROVEMENTS
WINCHESTER, VIRGINIA
PROJECT LAYOUT

CITY OF WINCHESTER VIRGINIA
ENGINEERING DIVISION
15 N. CAMERON STREET
WINCHESTER, VA 22601
PH: (540) 667-1815
FAX: (540) 662-3351



DRAWN BY:
rab


PROJECT NO:

SCALE:
1" = 20'

DATE:
3/17/16

SHEET:

3/ 5




HANDLEY BOULEVARD
IMPROVEMENTS
WINCHESTER, VIRGINIA
ELECTRICAL PLAN

**CITY OF
WINCHESTER
VIRGINIA**
ENGINEERING DIVISION
15 N. CAMERON STREET
WINCHESTER, VA 22601
PH: (540) 667-1815
FAX: (540)662-3351



DRAWN BY: PROJECT NO:
rab

SHEET: 4 / 5



SACRAMENTO Round Tapered/Non-Tapered Aluminum

Job Name: _____		Client Name: _____	
Job Location - City: _____	State: _____	Created By: _____	Date: _____
Product: SC12ASR - _____	Quote: _____	Customer Approval: _____	Date: _____

SPECIFICATIONS

Pole - The pole shaft is either spun or extruded from 6063 alloy aluminum.

Pole Top - A pole top plate and tenon are provided for top mount luminaire and/or bracket. A removable finial is available for poles receiving drilling patterns for side-mount luminaire arm assemblies.

Structural Base - The structural base is cast from 356 alloy aluminum and provided with a 3.00" wide X 5.50" tall access door. A grounding provision with hardware is provided. The pole is inserted and welded into the structural base casting. The completed assembly is heat-treated to a T6 temper after the structural welding is completed.

Anchor Bolts - Anchor bolts conform to ASTM F1554 Grade 55 and are provided with two hex nuts and two flat washers. Bolts have an "L" bend on one end and are galvanized a minimum of 12" on the threaded end.

Finish - The standard finish for the pole assembly and components is polyester powder applied coating in accordance with Valmont's Specifications. Additional finish options available upon request.

Design Criteria - Please reference Design Criteria Specification for appropriate design conditions.

VALMONT INDUSTRIES, INC.

28900 10A STREET, PO BOX 358 - VALLEY, NE 68064 USA


800.625.6688

VALMONTSTRUCTURES.COM

Pole - Aluminum

Sacramento

Round Tapered / Non-Tapered

		CITY OF WINCHESTER VIRGINIA		HANDLEY BOULEVARD IMPROVEMENTS		REVISIONS	
		ENGINEERING DIVISION 15 N. CAMERON STREET WINCHESTER, VA 22601		WINCHESTER, VIRGINIA			
		PH: (540) 667-1815					
		FAX: (540)662-3351					
							
DRAWN BY: rab		PROJECT NO:					
SCALE: 1" = 20'		DATE: 3/17/16					
SHEET:		5 / 5					